

M-30i

TaxCode
INFOSOLUTIONS

www.taxcode.gr

TECHNICAL SPECIFICATIONS

PRINT

Printing method	Direct thermal
Print speed	max. 100 mm/sec
Print width	max. 72 mm
Resolution	203 x 203 dpi
Sensors	Paper end, cover open

MEDIA

Media type	Thermal paper, linerless (optional)
Width	80 mm
Roll diameter	max. 50 mm
Media strength	max. 0.07 mm

ELECTRONICS

Memory	64 mbit SDRAM, 32 Mbit FlashROM
Interfaces	USB 2.0 FS, serial, Bluetooth 3.0 + DER
Battery	7.4 V Li-ion, 2,600 mAh, rechargeable
Barcodes	UPC-A, UPC-E, CODE 39, CODE 93, CODE 128, EAN 8, EAN 13, ITF, Codabar, PDF417, QR, Maxicode
Reliability	50 km (receipt roll), 10 km (linerless paper)

SOFTWARE

Drivers	Windows, OPOS, JPOS, Linux CUPS
Emulation	ESC / POS

SPECIFICATONS

Standard	Battery, belt clip, belt holster, battery charger, power cable, receipt roll, bag, CD, quick-start guide, cleaning pen
----------	--

WARRANTY

Period	24 month
--------	----------

HOUSING

Dimensions (WxHxD)	105 x 58 x 126 mm
Colour	Black

CONDITIONS

Temperature	Operating: -15 °C - 50 °C Storage: -30 °C - 70 °C
Humidity	Operating: 10 °C - 80 °C RH

HIGHLIGHTS

- + Top-speed receipt and label printing: 100 mm/sec.
- + Everything for an immediate start-up is included in the box
- + 1.8 m fall protection, as well as an IP54 rating with the optional protective case
- + Compatible with Android, Windows and Apple devices
- + Comprehensive selection of accessories, from a protective case to a magnetic stripe reader

